

## TECHNICAL INFORMATION

### 1. Product Name

Mirror Mastic: **Mirro-Mastic®**

### 2. Manufacturer

Palmer Products Corporation  
P.O. Box 7155  
Louisville, KY 40257  
Phone: 800.431.6151  
502.893.3668  
Fax: 502.895.9253  
Web site: [www.mirro.mastic.com](http://www.mirro.mastic.com)  
E-mail: [palmer@mirro.mastic.com](mailto:palmer@mirro.mastic.com)

### 3. Product Description

**Basic Use:** Mirro-Mastic® is a high quality adhesive mastic formulated for adhering plate glass mirror and acrylic mirror to various substrates.

### 4. Technical Data

**Composition and Materials:** Mirro-Mastic® is an asphalt base adhesive.

**Flash point:** Over 160°F (71.1°C)

**VOC Content:** 230g/L

**Color:** Black

**Application:** Electric Applicator, Mastic Stik or caulking gun

**Curing Time:** Curing time will depend on temperature, humidity, type of substrate and amount of air that can reach the mastic.

**Coverage:** With **minimum** coverage, one gallon will install approximately 130 square feet (12 square meters) of mirror, one 29 ounce cartridge will install approximately 30 square feet (2.8 square meters) of mirror, and one 11 ounce cartridge will install approximately 12 square feet (1.1 square meters) of mirror.

**Clean up:** Mineral spirits

**Storage:** Ideal storage 50°F to 85°F (10° to 29.4°C)

**Shelf Life:** Two years from the date on an unopened can. One year from the date on an unopened cartridge.

**Packaging:** 11 oz. cartridges (24 per case)  
29 oz. cartridges (12 per case)  
1 gallon cans (4 per case)  
5 gallon drums

### WARNING

All Palmer products must be used only for approved purposes, and must be applied in accordance with Palmer's installation instructions. The user bears all risk of damage, injury or other loss arising out of any non-approved use and/or improper installation of any Palmer product. If Palmer's installation instructions are not followed, in whole or part, for whatever reason, then mechanical fasteners of sufficient size and strength must immediately be used to insure safety of the installation pending prompt proper reinstallation by the product user. Any failure to properly utilize or apply any Palmer product may result in property damage, bodily injury or death. Palmer shall not be responsible for these or any other types of misuse of its products.