

JON GR Adhesive / Adhésif

FEATURES AND BENEFITS:

RS 020 is ideal for cleaning or thinning of Richelieu LIONGRIP Contact Adhesives. The product is specially formulated to provide for excellent clean-up of over spray and excessive adhesive residue. It will effectively dissolve wet or dried adhesive on laminate or other surfaces. It will be effective in cleaning up tools and equipment to include spray equipment, brushes, rollers, trays (first test the surface to ensure the cleaner is compatible).

RS 020 can also be used as an adhesive thinner if the contact cement has gotten older or heavier than normal. This can occur but leaving the lid off of a container or naturally by age. Use a small amount of RS 020 to dilute the contact by no more than 10 parts thinner to 100 parts adhesive. Over diluting can affect adhesive performance.

CHARACTERISTICS:

RS 020 is an effective cleaner and thinner for all Richelieu Contact Adhesives. It is an effective cleaner of over spray and contaminated surfaces.

PHYSICAL PROPERTIES:

Color: Clear -20°F Flash Point:

2 – 4 minutes Dry Time:

VOC: 761 grams/liter (EPA Method 24) Shelf Life: 1 year in unopened container

PACKAGING & COLOR:

RS 020 20 5 gal / 19 liters Clear

DIRECTIONS:

For cleaning: Wearing solvent resistant gloves is recommended during use. Using a soft, clean, dry towel. Wet the towel with solvent and wipe vigorously to clean overspray. This can be done while adhesive is wet or dry. If dry adhesive is not removed, attempt to soak the surface by first testing a small area to ensure the solvent does not harm the surface. If surfaces are proven safe, soak a small amount of cleaner onto the surface to be cleaned.

For cleaning tools and equipment, first test the cleaner to ensure it is compatible. Trays and brushes must be solvent resistant or cannot be cleaned. Allow brushes, rollers to soak overnight. Prior to using again, ensure solvent has been removed from the cleaned surface.

For thinning, always use small amounts of thinner, Never add more than 10% thinner or adhesive performance may be compromised. Agitation will be necessary for thinner to mix well with the adhesive - this will typically take 10 minutes of vigorous mixing. Test the mixed solution to ensure good bond quality after mixing.

DISCLAIMER OF WARRANTY

APPLICATION:

A clear solvent recommended for thinning and cleaning most extremely flammable contact adhesives. Can also be used for cleaning brushes, rollers, equipment parts and for flushing through spray lines and spray guns.

In thinning adhesive, add a small quantity of solvent while thoroughly mixing until the desired consistency is reached. Be careful not to add too much solvent and/or add solvent too fast.

In cleaning adhesive off substrates, DO NOT flood the area with solvent as it can work into seams and soften the adhesive and cause delaminating. Use a cloth that is saturated with solvent, but not dripping. Keep the solvent exposure to edges and seams of the lamination at a minimum to avoid softening the bond line.

APPLICATION PRECAUTIONS:

Liquid and vapor are extremely flammable.

STORAGE:

Keep container closed tightly when not in use.